



## Kodak Versamark DS5300 printing system

### Fast, flexible, variable data imaging system

#### Modular, easy to merge technology

The Kodak Versamark DS5300 is a digital printing system with a print width of 2.77 inches (7.03 cm) that features: letter-quality, crisp character definition; flexibility in font selection and positioning; pinpoint registration at speeds of up to 500 fpm (150 mpm); and resolutions of 300 x 300 or 300 x 600 dpi.

The DS5300 meets a wide range of variable data imaging application needs including business forms, tag and label, direct mail, booklets and billing statements. It is ideal for barcoding, numbering, addressing, personalization and spot color.

The DS5300 is modular, making it easy to merge with web or sheet-fed presses, collators, mail bases, folders and a variety of other in-line and off-line equipment. The components include:

- A Kodak Versamark CS400 system controller, a Windows XP-based operator interface with MPC data prep software
- From one to 16 Kodak Versamark DT2 print stations
- From one to four Kodak Versamark CD120 data stations (each can drive up to four print stations)
- Optional mounting packages

## PRINTHEAD

Printheads are replaceable components that connect to the print station through an umbilical. Resolutions are either 300 x 300 or 300 x 600 dpi, user selectable.

### *DH5300 printhead*

#### *Physical specifications*

Height: 19" (48.26 cm)  
Width: 8" (20.32 cm)  
Depth: 8" (20.32 cm)  
Print array width: 2.77" (7.03 cm)  
Image speed: Up to 500 feet  
(150 m) per minute,  
based on application

## UMBILICAL

The DH5300 printhead connects to the body of the print station through an umbilical.

### *Flexible umbilical*

Length: 40 feet (12.19 m)  
Fluid containers (external)  
Ink: 5.2 gal. (20 liters)  
55 gal. (209 liters) drum

## PRINTER PHYSICAL/ELECTRICAL

### *DT2 print station cabinet*

Height: 49" (125 cm)  
Width: 22" (56 cm)  
Depth: 32.5" (83 cm)  
Weight: 380 lbs. (172.52 kg)  
without monitor, keyboard and umbilical

### *DT2 print station power requirements*

180–250 VAC  
10 amp  
47/63 Hz  
3-wire, single-phase (U.S.)

### *System controller/data station cabinet*

Height: 40" (102 cm) without monitor  
58" (147 cm) with monitor  
Width: 36" (91.5 cm) includes top  
work surface  
Depth: 32" (81.3 cm) door closed  
55" (140 cm) door opened  
Weight: 400 lbs. (180 kg)

## ENVIRONMENTAL OPERATING RANGES

Temperature: 60°F–85°F (15.5°C–29.4°C)  
Relative humidity: 10%–90%, non-condensing  
Temperature: 86°F–104°F (30°C–40°C)  
Relative humidity: 10%–60%

## OPTIONS

Printhead mounting package  
512 MB font memory  
I/O box with six user output signals



Kodak Versamark, Inc.  
© Eastman Kodak Company, 2004.  
Kodak and Versamark are trademarks of Eastman Kodak Company.

For more information on Kodak Versamark printing solutions, contact your local sales representative, call us at 800.472.4839 or visit our website at [www.kodakversamark.com](http://www.kodakversamark.com).  
Kodak Versamark, Inc. / 3000 Research Boulevard / Dayton, Ohio 45420-4003 / U.S.A.  
Tel: 937.259.3000 / Fax: 937.259.3385